

DC FAN

JAMICON®

120X120X25 mm



SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating (V)	Air Flow (CFM)	Static Pressure (mmH ₂ O)	Speed (R.P.M)	Rated Current (Amp)	Input Power (Watt)	Noise (dBA)	Life Expectancy (Hour)	Weight (g)
JF1225B1L	B	12	10.2~ 13.8	67.43	3.02	1800	0.20	2.40	33.1	66000	135
JF1225S1L	S			67.43	3.02	1800	0.20	2.40	33.1	40000	
JF1225B1M	B			74.25	4.05	2100	0.25	3.00	37.3	57000	
JF1225S1M	S			74.25	4.05	2100	0.25	3.00	37.3	34000	
JF1225B1H	B			82.97	4.72	2400	0.30	3.60	41.1	50000	
JF1225S1H	S			82.97	4.72	2400	0.30	3.60	41.1	30000	
JF1225B2L	B	24	20.4~27.6	67.43	3.02	1800	0.15	3.60	33.1	66000	
JF1225S2L	S			67.43	3.02	1800	0.15	3.60	33.1	40000	
JF1225B2M	B			74.25	4.05	2100	0.2p	4.80	37.3	57000	
JF1225S2M	S			74.25	4.05	2100	0.2p	4.80	37.3	34000	
JF1225B2H	B			82.97	4.72	2400	0.25	6.00	41.1	50000	
JF1225S2H	S			82.97	4.72	2400	0.25	6.00	41.1	30000	
JF1225B4L	B	48	28.0~60.0	67.43	3.02	1800	0.06	2.88	33.1	66000	
JF1225S4L	S			67.43	3.02	1800	0.06	2.88	33.1	40000	
JF1225B4M	B			74.25	4.05	2100	0.08	3.84	37.3	57000	
JF1225S4M	S			74.25	4.05	2100	0.08	3.84	37.3	34000	
JF1225B4H	B			82.97	4.72	2400	0.10	4.80	41.1	50000	
JF1225S4H	S			82.97	4.72	2400	0.10	4.80	41.1	30000	

Specifications Subject to change without notice

- Frame: Plastic Material UL 94V-0
- Blade: Plastic Material UL 94V-0
- Insulation Resistance: 50M ohm min. at 500 VDC (between frame and terminal)
- Dielectric Strength: 5mA max. at 500 VAC 60 Hz one minute (between frame and terminal)
- Operating Temperature: -10°C to +70°C
Option: -20°C to +80°C

